

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

1141/61930

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)

09/554155

INTERNATIONAL APPLICATION NO.

PCT/JP98/05406

INTERNATIONAL FILING DATE

12/01/98

PRIORITY DATE CLAIMED

12/01/97

TITLE OF INVENTION

MAGNET APPARATUS AND MRI APPARATUS

APPLICANT(S) FOR DO/EO/US

1) Hitachi Medical Corporation 2) Hitachi, Ltd.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
 2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
 3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(I).
 4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
 5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
 6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
 7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☒ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
 8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
 9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
 10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).
- Items 11. to 16. below concern document(s) or information included:
11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
 12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
 13. ☐ A **FIRST** preliminary amendment.
 - ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
 14. ☐ A substitute specification.
 15. ☐ A change of power of attorney and/or address letter.
 16. ☒ Other items or information: Express Mail Certificate; copy of PCT/JP98/05406 filed 12/01/98; copy of International Search Report; English translation of Search Report (dated December 22, 1998) and cited references; English translation of the International Application as filed.

Dkt. 1141/61930

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of: KAKUGAWA, et al.

Serial No. : 09/554,155

Group Art Unit:

Date Filed : May 9, 2000

Examiner:

For : MAGNET APPARATUS AND MRI APPARATUS

1185 Avenue of the Americas
New York, N.Y. 10036

Assistant Commissioner for Patents

Box PCT

Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Please amend the application as follows:

In the Claims:

Please add new claims 22-65 as follows:

--22. (New) A magnet device according to claim 4, characterized in that each of the static magnetic field generation sources includes at least one ferromagnetic body which helps formation of the magnetic field.--

I hereby certify that this paper is being deposited this date with the U.S. Postal Service as first class mail addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Ivan S. Kavrukov

Aug 15, 2000

Ivan S. Kavrukov
Reg. No. 25,161

Date

--23. (New) A magnet device according to claim 5, characterized in that each of the static magnetic field generation sources includes at least one ferromagnetic body which helps formation of the magnetic field.--

--24. (New) A magnet device according to claim 6, characterized in that each of the static magnetic field generation sources includes at least one ferromagnetic body which helps formation of the magnetic field.--

--25. (New) A magnetic device according to claim 19, characterized in that the ferromagnetic body functions as a magnetic pole.--

--26. (New) A magnetic device according to claim 20, characterized in that the ferromagnetic body functions as a magnetic pole.--

--27. (New) A magnetic device according to claim 21, characterized in that the ferromagnetic body functions as a magnetic pole.--

--28. (New) A magnetic device according to claim 22, characterized in that the ferromagnetic body functions as a magnetic pole.--

--29. (New) A magnetic device according to claim 23, characterized in that the ferromagnetic body functions as a magnetic pole.--

--30. (New) A magnetic device according to claim 24, characterized in that the ferromagnetic body functions as a magnetic pole.--

--31. (New) A magnet device according to claim 1, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.--

--32. (New) A magnet device according to claim 2, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.--

--33. (New) A magnet device according to claim 3, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.--

--34. (New) A magnet device according to claim 4, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.--

--35. (New) A magnet device according to claim 5, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.--

--36. (New) A magnet device according to claim 6, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.--

--37. (New) A magnet device according to claim 31, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped ferromagnetic body.--

--38. (New) A magnet device according to claim 32, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped

ferromagnetic body.--

--39. (New) A magnet device according to claim 33, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped ferromagnetic body.--

--40. (New) A magnet device according to claim 34, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped ferromagnetic body.--

--41. (New) A magnet device according to claim 35, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped ferromagnetic body.--

--42. (New) A magnet device according to claim 36, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped ferromagnetic body.--

--43. (New) A magnet device according to claim 1, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying

means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.--

--44. (New) A magnet device according to claim 2, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.--

--45. (New) A magnet device according to claim 3, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.--

--46. (New) A magnet device according to claim 4, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.--

--47. (New) A magnet device according to claim 5, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.--

--48. (New) A magnet device according to claim 6, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.--

--49. (New) An MCI device which uses the magnet device according to claim 1.--

--50. (New) An MCI device which uses the magnet device according to claim 2.--

--51. (New) An MCI device which uses the magnet device according to claim 3.--

--52. (New) An MCI device which uses the magnet device according to claim 4.--

--53. (New) An MCI device which uses the magnet device according to claim 5.--

--54. (New) An MCI device which uses the magnet device according to claim 6.--

--55. (New) An MCI device including the magnet device according to claim 1, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of a stand on which a measurement object is laid.--

--56. (New) An MCI device including the magnet device according to claim 2, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of a stand on which a measurement object is laid.--

--57. (New) An MCI device including the magnet device according to claim 3, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of the stand on which a measurement object is laid.--

--58. (New) An MCI device including the magnet device according to claim 4, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of a stand on which a measurement object is laid.--

--59. (New) An MCI device including the magnet device according to claim 5, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of a stand on which a measurement object is laid.--

--60. (New) An MCI device including the magnet device according to claim 6, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of a stand on which a measurement object is laid.--

--61. (New) A super conducting magnetic device for an open and vertical magnetic field type MCI device including a first and a second static magnetic field generation source which are disposed in vertical direction opposing each other while sandwiching a space for receiving a person to be inspected, each of the first and second static magnetic field generation sources includes static magnetic field generation use coil units of equal to or more than three which are arranged concentrically around the center axis in vertical direction thereof, characterized in that, the directions of DC current flow in the static magnetic field generation use coil units of equal to or more than three in each of the static magnetic field generation sources are determined alternative in positive and negative direction with reference to projection positions of geometric centers of cross sections of the respective coil units of equal to or more than three on a straight line passing through a crossing point, on a plane which is perpendicular to the center axis in vertical direction and contains a horizontal axis having an equal distance both from the first and second static magnetic field generation sources, of the center axis and the horizontal axis and at the side of the straight line away from the horizontal axis when viewed from the respective coil units of equal to or more than three.--

--62. (New) A super conducting magnet device for an open and vertical magnetic field type MCI device including a pair of static magnetic field generation sources which are disposed in vertical

direction opposing each other while sandwiching a space having a broad opening for receiving a person to be inspected, and each of the pair of static magnetic field generation sources includes a main coil unit for the static magnetic field generation having a first diameter and being disposed concentrically with the center axis in vertical direction thereof, a plurality of coil units for irregular magnetic field correction each having a diameter smaller than the first diameter and being likely disposed concentrically with the center axis in vertical direction thereof and a shielding coil unit for suppressing magnetic field leakage having substantially the same diameter as the first diameter and being disposed concentrically with the center axis in vertical direction thereof but being located distant position than the main coil unit for static magnetic field generation with respect to the space, characterized in that, the directions of DC current flow in the main coil unit for static magnetic field generation and the plurality of coil units for irregular magnetic field correction in each of the static magnetic field generation sources are determined alternative in positive and negative direction with reference to projection positions of geometric centers of cross sections of the main coil unit for static magnetic field generation and the plurality of the coil units for irregular magnetic field correction on a straight line passing through a crossing point, on a plane which is perpendicular to the center axis in vertical direction and contains a horizontal axis having an equal distance both from the first and second static magnetic field generation sources, of the center axis and the horizontal axis and at the side of the straight line away from the horizontal axis when viewed from the main coil unit for static magnetic field generation and the plurality of coil units for irregular magnetic field correction, as well as the direction of DC current flow in the shielding coil unit is determined to be opposite to the direction of the DC current flow in the main coil unit for static magnetic field

generation.--

--63. (New) A magnetic device including a pair of static magnetic field generation sources for generating a uniform magnetic field directing in a first direction in a finite region each of the static magnetic field generation sources being provided with at least two current carrying means disposed concentrically, characterized in that, the at least two current carrying means are disposed concentrically while being spaced each other and further when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the respective static magnetic field generation sources as a first point, the current carrying means are disposed in such a manner that when geometrical centers of cross sections of the current carrying means are projected on a first straight line on a first plane containing the first axis, the second axis and the first point and passing through the first point, the current carrying means at the respective corresponding projections aligns alternatively in positive and negative direction on the first straight line.--

--64. (New) A super conducting magnetic device for an open and vertical magnetic field type MCI device including a first and a second static magnetic field generation source which are disposed opposing each other while sandwiching a space for receiving a person to be examined, each of the first and second static magnetic center axis passing through the center thereof, characterized in that, the static magnetic field generation use coil units of equal to or more than three in each of the static

magnetic field generation sources are arranged in such a manner that within an angle range defined by a first line segment on a plane containing the center axis and extending in a direction perpendicular to the center axis from a center point on the center axis having substantially the same distance from both first and second static magnetic field generation sources and a second line segment extending from the center point toward the static magnetic field generation use coil unit located most inside and most close with respect to the space within the plane, when the geometric centers of the cross sections of the respective static magnetic field generation use coil units are projected on any straight line while locating the first line segment therebetween, the current flow directions of the static magnetic field generation use coil units at the respective corresponding projection points align alternatively in positive and negative direction on the straight line.--

--65. (New) A super conducting magnet device for an open and vertical magnetic field type MCI device including a pair of static magnetic field generation sources which are disposed opposing each other while sandwiching a space having a broad opening for receiving a person to be examined, and each of the pair of static magnetic field generation sources includes a main coil unit for the static magnetic field generation having a first diameter and being disposed concentrically with the center axis passing the center of the static magnetic field generation sources, a plurality of coil units for irregular magnetic field correction each having a diameter smaller than the first diameter and being disposed concentrically with the center axis thereof and a shielding coil unit for suppressing magnetic field leakage having substantially the same diameter as the first diameter and being disposed concentrically with the center axis thereof but being located distant position than the main

coil unit for static magnetic field generation with respect to the space, characterized in that, the main coil unit for static magnetic field generation and the plurality of coil units for irregular magnetic field correction in each of the static magnetic field generation sources are arranged in such a manner that within an angle range defined by a first line segment on a plane containing the center axis and extending in a direction perpendicular to the center axis from a center point on the center axis having substantially the same distance from both first and second static magnetic field generation sources and a second line segment extending from the center point toward the coil unit for irregular magnetic field correction located most inside and most close with respect to the space within the plane, when the geometric centers of the cross sections of the main coil unit for static magnetic field generation and the plurality of unit coils for irregular magnetic field correction are projected on any straight line while locating the first line segment therebetween, the current flow directions of the main coil unit for static magnetic field generation and the plurality of unit coils for irregular magnetic field correction at the respective corresponding projection points align alternatively in positive and negative direction on the straight line as well as the direction of DC current flow in the shielding coil unit is determined to be opposite to the direction of the DC current flow in the main coil unit for static magnetic field generation.--

REMARKS

Claims 1-65 are pending in this application.

The Office is hereby authorized to charge any fees that may be required in connection with this preliminary amendment and to credit any overpayment to our Deposit Account No. 03-3125.

If a petition for an extension of time is required to make this response timely, this paper should be considered to be such a petition, and the Commissioner is authorized to charge the requisite fees to our Deposit Account No. 03-3125.

If a telephone interview could advance the prosecution of this application, the Examiner is respectfully requested to call the undersigned attorney.

Entry of this preliminary amendment and allowance of this application are respectfully requested.

Respectfully submitted,



Ivan S. Kavrukov
Reg. No. 25,161
Attorney for Applicants
Cooper & Dunham LLP
Tel.: (212) 278-0400

416 Rec'd PCT/PTO 09 MAY 2000

1

TITLE OF THE INVENTION

Magnet Apparatus and MRI Apparatus

FIELD OF THE INVENTION

5 The present invention relates to a super
conducting magnet which is suitable for a nuclear
magnetic resonance imaging (hereinafter, simply called
as MRI) device, and, more specifically, relates to a
super conducting magnet device which is provided with
10 a broad opening as well as makes easy to access to a
measurement object by reducing the outer diameter of
the magnet.

BACKGROUND ART

15 Conventionally, it was difficult that a person
performing inspection such as a medical doctor
accesses a person under inspection during image taking
with an MRI device, therefore, the so called
Interventional Radiology (hereinafter, simply called
20 as IVR) was as well as difficult.

For example, JP-A-7-106153 (1995) entitled "C
Type Super Conducting Magnet" discloses a conventional
art for avoiding the above problems.

The above referred to device takes MRI images
25 after inserting a patient between two magnetic poles.

This device is for generating a uniform magnetic
field by optimizing the configuration of the magnetic

poles, however, because of weight limitation thereof, a uniform magnetic field space which can be used merely for inspecting a head portion of the patient is generally created.

5 However, in a case of whole-body use MRI device which permits an image taking of such as the abdomen, the chest and the bi-shoulder of a patient representing an inspection object without moving the patient during image taking, it is generally necessary
10 to generate a uniform magnetic field with intensity variation of a few ppm (for example 2~3 ppm) in an image taking region covered by a sphere having a diameter from 40cm to more than 50cm. Accordingly, it is required to develop an MRI device having a magnet
15 which can generates a uniform magnetic field with its intensity variation of a few ppm (for example, 2~3 ppm) in an image taking region covered by a sphere having a diameter from 40cm to more than 50cm while keeping a highly open space feeling in the magnet for
20 an MRI device.

As has been explained above, it was difficult until now to generate a uniform magnetic field over a broad region in a magnet having a broad opening which gives an open space feeling for a person to be
25 inspected (a patient) representing a measurement (image taking) object. Further, there is a problem to have to increase the outer diameter of the magnet in

order to obtain a broad uniform magnetic field space, which causes other problems to deteriorate the open space feeling for the patient and easy access thereto. Still further, when it is intended to enlarge the
5 uniform magnetic field region, which causes a problem of increasing the manufacturing cost of the magnet because the absolute value of magnetomotive forces of coils constituting the magnet has to be increased.

Further, JP-A-3-141619 (1991) discloses a magnet
10 for generating a uniform magnetic field in a broad region in which currents in opposite directions are flown through two coils disposed in outside and inside along a same axis to generate magnetic fields in opposite direction and to superposed the same each
15 other, thereby, a non-uniformity of magnetic field produced by a single coil is canceled out to enlarge a uniform magnetic field region.

Further, JP-A-9-153408 (1997) applied by the present applicants discloses a super conducting magnet
20 device each of a pair of static magnetic field generation sources disposed in vertical direction so as to oppose each other is constituted so as to include one main coil unit for generating static magnetic field and a plurality of coil units for
25 correcting irregular magnetic field, however, JP-A-9-153408 (1997) does not disclose specifically the DC current flow direction in these two sorts of unit

coils.

SUMMARY OF THE INVENTION

An object of the present invention is to provide
5 a super conducting magnet with a broad opening used
for unclear magnetic resonance which generates a
desirable uniform magnetic field in comparison with a
conventional magnet and shows a high open space
feeling through a small outer diameter of the magnet.

10 A first aspect of the magnet device according to
the present invention which achieves the above object
and in which two sets of static magnetic field
generation sources, each being constituted by current
carrying means disposed substantially concentrically
15 with respect to a first direction in order to generate
a uniform magnetic field directing in the first
direction in a finite region, are disposed facing each
other while placing the uniform magnetic field region
therebetween and each of the static magnetic field
20 generation sources is provided with at least four
current carrying means, is characterized in that when
assuming a crossing point of a first axis which is in
parallel with the first direction and passes
substantially the center of the current carrying means
25 and a second axis which crosses the first axis
orthogonally and locates at substantially the equal
distance from the two sets of the static magnetic

field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, 5 the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying 10 means corresponding to the respective projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction.

A second aspect of the magnet device according to 15 the present invention in which two sets of static magnetic field generation sources, each being constituted by current carrying means and shielding current carrying means for suppressing leakage magnetic field to an external region disposed 20 substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and 25 each of the static magnetic field generation sources is provided with at least four current carrying means and at least one shielding current carrying means, is

characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means corresponding to the respective projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction.

A third aspect of the magnet device according to the present invention in which two sets of static magnetic field generation sources, each being constituted by current carrying means disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing

the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with a ferromagnetic body functioning as a magnetic pole and at least two current carrying means, 5 is characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at 10 substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing 15 through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the 20 current carrying means corresponding to the respective projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction.

A fourth aspect of the magnet device according to 25 the present invention in which two sets of static magnetic field generation sources, each being constituted by current carrying means and shielding

current carrying means for suppressing leakage magnetic field to an external region disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with a ferromagnetic body functioning as a magnetic pole, at least two current carrying means and at least one shielding current carrying means, is characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means corresponding to the respective

projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction.

A fifth aspect of the magnet device according to the present invention in which two sets of static magnetic field generation sources, each being constituted by current carrying means disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with three current carrying means, is characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying

means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means corresponding to the respective projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction.

A sixth aspect of the magnet device according to the present invention in which two sets of static magnetic field generation sources, each being constituted by current carrying means and shielding current carrying means for suppressing leakage magnetic field to an external region disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with three current carrying means and at least one shielding current carrying means, is characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a

first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means
 5 are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means corresponding to the respective
 10 projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction.

Now, magnetic field in a magnet used in an MRI device will be explained thereinbelow.

15 When assuming that the center axis of the magnet device is z axis, r and θ represent a coordinate position in a polar coordinate assuming the center of the magnet device as origin and $P_n(\cos \theta)$ is Legendre's function of nth degree, magnetic field Bz
 20 in z direction near the center portion of the magnet device can generally be developed and expressed in the following equation (1);

$$B_z = \sum_{n=0}^{\infty} d_n r^n P_n(\cos \theta) \quad \cdots (1)$$

wherein d_0 is a uniform magnetic field and $d_1, d_2, d_3,$
 25 $d_4, d_5, d_6 \cdots$ are irregular magnetic field intensities

which deteriorate uniformity of the magnetic field. When the magnet is arranged symmetric with respect to the center plane thereof, $d_1, d_3, d_5 \dots$ among the above irregular magnetic field components become zero because of the symmetry nature. Accordingly, only the irregular magnetic field components $d_2, d_4, d_6 \dots$ are required to take into account as the irregular magnetic fields which deteriorate uniformity of the magnetic field.

10 An MRI use magnet is required to form a uniform magnetic field having a few ppm order variation in an image taking region near the magnet center portion. A uniform magnetic field generation is achieved by successively eliminating the irregular magnetic field components $d_2, d_4, d_6 \dots$ from lower degree terms among developed terms according to equation (1) expressing a magnetic field in z direction near the center portion of the magnet. Form equation (1) it will be understood that if the irregular magnetic field components are eliminated up to high degree terms, a space of uniform magnetic field will be expanded.

A magnet device for an MRI device used such as in hospitals is required to generate a uniform magnetic field within $\pm 5\text{ppm}$ variation rate in a spherical region having a diameter of 40cm~50cm.

In order to fulfill the above requirement, proper magnet designs are usually employed so that the

irregular magnetic field components from the second degree to 8th degree or 10th degree in that d_2 , d_4 , d_6 , d_8 and d_{10} become zero.

As has been explained above, in order to generate
 5 a uniform static magnetic field, at first it is necessary to make zero the second degree irregular magnetic field component d_2 .

For the sake of simplicity, a magnetic field formed by an annular ring line current is discussed.
 10 Among developed terms expressed by the equation (1) of the magnetic field produced by the annular ring line current as shown in Fig. 13, plots of d_2 depending on $\beta=a/b$ are shown in Fig. 14. Wherein, a represents a radius of the annular ring line current, b represents
 15 a distance of the annular ring line current from the origin in z axis direction and i represents a current value, and in the plots it is assumed that $b=1$ and $i=1$. As will be apparent from Fig. 14, the developed term coefficient d_2 becomes zero when $\beta=2$, in other
 20 words, the second degree irregular magnetic field component becomes zero with the arrangement which is already known as a Helmholtz coil.

In an MRI device use magnet, it is necessary to eliminate at first the secondary degree irregular
 25 magnetic field component as has been explained above, however, as will be understood from Fig. 14, if coils

through which currents in the same direction flow are only used, it is impossible to reduce the coil diameter than that of the Helmholtz coil arrangement.

Accordingly, two annular ring currents each
 5 having β smaller than 2 as shown in Fig. 15 are discussed. Wherein, it is assumed that a radius and current value of an annular ring current 175 are respectively a_1 and $i=1$, and a radius and current value of an annular ring current 176 are respectively
 10 a_2 and $i=-0.4$. Values of d_2 produced respectively by the two coils depending on β are plotted in Fig. 16. Curves 177 and 178 respectively correspond to the annular ring currents 175 and 176. As will be apparent from Fig. 16, if the values β_1 and β_2 are
 15 properly selected, it is possible to make the absolute values of respective d_2 terms produced by the annular ring currents 175 and 176 equal, but the signs thereof to be opposite each other, thereby, the sum of irregular magnetic field components d_2 produced by the
 20 two annular ring currents 175 and 176 can be rendered zero. Namely, through an arrangement of a plurality of coils each having different polarity in alternative manner in radial direction the secondary degree irregular magnetic field component can be eliminated
 25 with coils having a smaller outer diameter than that of a Helmholtz coil.

Now, an exemplary arrangement in which the secondary and quadratic degree irregular magnetic field components are eliminated will be explained. Fig. 21 shows an optimum designed coil arrangement 5 which is determined through computer programs so as to minimized the sum of absolute values of magnetomotive force according to the present invention. As is illustrated in Fig. 21, in order to eliminate irregular magnetic field components up to the 10 quadratic degree and to reduce the outer diameter of the coils than the arrangement of a Helmholtz coil, total of six pieces of coils is necessary, in that three for one of two static magnetic field generation sources and other three for the other static magnetic 15 field generation source. Coils of which current flow direction are positive and negative are alternatively arranged in the radial direction. The absolute values of magnetomotive force are increased according to the radial diameter size thereof.

20 How the secondary and quadratic degree irregular magnetic field components are eliminated in this coil arrangement will be explained with reference to Figs. 22 and 23.

Fig. 22 shows secondary degree irregular magnetic 25 field components produced by the respective coils shown in Fig. 21, and Fig. 23 shows quadratic degree irregular magnetic field components produced by the

respective coils as shown in Fig. 21. Curves 211, 212 and 213 are sensitivity curves relating to secondary degree irregular magnetic field components corresponding to magnetomotive forces produced by coils #1, #2 and #3 in Fig. 21 with respect to β . Curves 214, 215 and 216 are sensitivity curves of the quadratic degree irregular magnetic field components corresponding to the magnetomotive forces of the coils #1, #2 and #3 as shown in Fig. 21 with respect to β .

The values β of geometric centers of the cross sections of the coils #1, #2 and #3 are respectively 0.30, 0.80 and 1.46. Accordingly, the secondary degree irregular magnetic field component produced by, for example, coil #3 assumes the value indicated by the numeral 203. Accordingly, with the coil arrangement of Fig. 21 the coils #1, #2 and #3 respectively produce the secondary degree irregular magnetic field components as indicated by numerals 201, 202 and 203 in Fig. 22, and the positions and magnetomotive forces of the respective coils are set so that the sum of these secondary degree irregular magnetic field components is rendered zero. Likely, the coils #1, #2 and #3 respectively produce the quadratic degree irregular magnetic field components as indicated by numerals 204, 205 and 206 in Fig. 23, and the positions and magnetomotive forces of the respective coils are set so that the sum of these

quadratic degree irregular magnetic field components is rendered zero.

These relationships can be qualitatively explained as follows. As has been explained above, at first it is necessary to eliminate the secondary degree irregular magnetic field components, for this reason, the positions of coils #2 and #3 are mostly determined on this base. Although the coil #3 produces the quadratic degree irregular magnetic field component as indicated by the numeral 206 to be eliminated, however, as seen from the sensitivity curves in Figs. 22 and 23, it will be understood that no solution which renders both the secondary and quadratic degree irregular magnetic field components zero can not exist, only when the positions and the magnetomotive forces of the coils #2 and #3 are varied. Accordingly, the coil #1 is newly added of which radius is the smallest and of which magnetomotive force is directed positive to produce the quadratic degree irregular magnetic field component indicated by the numeral 204, thereby, the total sum of quadratic degree irregular magnetic field components is reduced zero. Further, in order to minimize the sum of absolute values of magnetomotive forces, the positions of the respective coils are determined in such a manner that the positions corresponding near to the peaks of the respective

sensitivity curves are avoided and the positions showing as much as small sensitivity are selected. Actually, since the coil #1 produces the secondary degree irregular magnetic field component as indicated
5 by the numeral 201, it is necessary to adjust to render the secondary degree irregular magnetic field components zero as a whole as well as the quadratic degree irregular magnetic field components zero, accordingly an optimum arrangement of the coils is
10 correctly determined through computer programs incorporating the sensitivity curves. In order to eliminate the secondary and quadratic degree irregular magnetic field components with group of coils each having a smaller radius than that of a Helmholtz coil,
15 it is necessary to arrange coils with positive and negative current flow directions alternatively as has been explained above, this is because the sensitivity curves of irregular magnetic field components of respective degrees show the shapes as illustrated in
20 Fig. 19. The respective sensitivity curves are physically and inherently determined based on an electro-magnetic phenomenon. The present invention is brought about on the analysis of the sensitivity curves, accordingly, the result of the present
25 invention which is obtained by making use of the analysis is non-ambiguously determined.

Although in the present embodiment a specific

explanation on elimination of the irregular magnetic
 field components of higher degree equal to and more
 than 6 degree is omitted, the same principle can be
 applied thereto, in that through the alternate
 5 arrangement of coils having different polarity in the
 radial direction thereof, a magnet of which irregular
 magnetic field components are eliminated up to high
 degrees and which generates an extremely uniform
 magnetic field can be constituted with a magnet having
 10 a smaller outer diameter than that of a Helmholtz coil.
 Further, the present structure provides a minimum
 number of coils which eliminates the irregular
 magnetic field components up to necessary degree,
 accordingly, the sum of the absolute values of
 15 magnetomotive forces of the respective coils shows
 minimum among any conceivable coil arrangement.

The above coil arrangement can be determined
 through computer programs making use of the
 sensitivity curves of the irregular magnetic field
 20 intensities of respective degrees as shown in Fig. 19.
 Since it is difficult to explain the function thereof,
 the nature of the solution is qualitatively explained.
 Fig. 20 shows a general space distribution of sixth
 degree irregular magnetic field intensity. In the
 25 drawing, the origin represents the center of the
 magnet, z axis corresponds to the center axis of the
 magnet, ρ axis represents an axis in radial direction

which passes through the center of the magnet and is directed to an arbitrary direction, and the abscissa represents sixth degree irregular magnetic field intensity. As will be understood from the equation (1) referred to previously, the intensity at the origin is zero and the intensity increases in proportion to 6th power of the distance according to the distance increase from the origin. However, depending on the nature of $P_n(\cos \theta)$ the intensity is expressed by a space distribution having positive and negative values with respect to azimuth angle θ . Accordingly, for example, with regard to the space distribution of 6th degree irregular magnetic field component through alternative arrangement of coils having positive and negative polarity, the 6th degree irregular magnetic field component can be effectively canceled out. The alternative arrangement of coils having positive and negative polarity can be generalized in such a manner that when geometric centers of cross sections of respective coils are projected on a straight line passing through the origin, current polarity of the coils corresponding to the projected centers is aligned alternatively in positive and negative on the straight line as will be defined in claims.

Now, advantages of the present invention will be specifically explained by making use of numerical

calculation result. Fig. 17 shows a calculation result based on the principle of the present invention and at the same time illustrates a coil arrangement and contours representing magnetic field uniformity.

- 5 The respective contours of magnetic field uniformity indicate ± 1 , ± 5 and ± 10 ppm from the inside. Wherein, the current density in the coils is 100A/mm^2 , the interval between the upper and lower coils is 1.0m and the outer diameter of the coils is limited to 1.7m .
- 10 Further, the intensity of the center magnetic field is 0.4T and the second through 6th degree irregular magnetic field components are rendered zero near the center portion.

- As will be apparent from Fig. 17, when the
- 15 geometric centers of the respective coil cross sections on $z-\rho$ plane in the first quadrant are projected on the ρ axis, the current flow directions at the projected centers corresponding to the respective coils are aligned alternatively in positive
- 20 and negative. With the arrangement method according to the present invention the sum of absolute values of magnetomotive force by the respective coils is minimized, namely, the present method is understood the most reasonable one.

- 25 Fig. 18 shows one of calculation results not based on the principle of the present invention.

The current density in the coils, the intensity

of the center magnetic field, and the degrees of canceled out irregular magnetic field components are substantially the same as these of Fig. 17. In the calculation example in Fig. 18, when the geometrical
5 centers of the respective coil cross sections on z - ρ plane are projected on any straight lines on the z - ρ plane passing the origin, their current flow directions at the projected centers corresponding to the respective coils are never aligned alternatively
10 in positive and negative, namely, Fig. 18 arrangement never follows the principle of the present invention. When comparing the calculation example of Fig. 18 with the calculation example of Fig. 17, their space distributions of generated magnetic field are
15 substantially the same, however, in Fig. 18 calculation example requires 1.4 times of the sum of absolute values of magnetomotive force produced by the coils for achieving the same space magnetic field distribution and further requires two more coils in
20 total. Namely, the most advantageous effect of the present invention is to provide a coil arrangement which shows the minimum sum of absolute value of magnetomotive force among possible coil arrangements which produce a magnetic field distribution having a
25 predetermined space distribution. In the coil arrangement as shown in Fig. 18 which does not follow the principle of the present invention, since the sum

of absolute values of magnetomotive force of the coils is 1.4 times larger when compared with the coil arrangement as shown in Fig. 17 which follows the principle of the present invention and the number of
5 coils also increases by 2, a variety of demerits are caused such as an increase of electro-magnetic force between coils, complexing of support structure and weight increase thereby and weight increase of cooling means, and as a result, production cost of the magnet
10 extremely increases, therefore, it is understood that the conventional design method as exemplified in Fig. 18 is very inefficient one. Further, in the calculation result as shown in Fig. 17 which is based on the principle of the present invention, the
15 absolute value of magnetomotive force of a coil having the largest average radius is larger than the absolute values of magnetomotive force of other coils and it is further understood that when the respective coils in the first quadrant is projected on ρ axis, the
20 absolute values of magnetomotive force of the respective coils are aligned according to the magnitudes thereof. These setting methods of the magnetomotive forces are also conditions which minimizes the sum of absolute values of magnetomotive
25 force of the entire coils.

Further, a magnet device for an open type MRI device as disclosed in U.S. Patent No.5,410,287 is

directed to a horizontal magnetic field type, however, the coil arrangement therein is somewhat similar to that explained in connection with Fig. 18.

Further, for a whole-body MRI it is necessary to
5 generate a uniform static magnetic field having variation within ± 5 ppm in a spherical region having a diameter of 40cm~50cm. For this requirement it is necessary to make zero at least up to 8th degree irregular magnetic field components, and for the
10 purpose of design freedom at least four coils are necessary for each magnet assembly. In a coil design which eliminates irregular magnetic field components up to 6th degree, 8th degree irregular magnetic field component dominantly controls the magnetic field
15 uniformity, therefore, it is necessary to reduce the intensity of the 8th irregular magnetic field as much possible, and for this necessary it is preferable to limit the magnetomotive force produced by the respective coils. Although not illustrated as
20 calculation examples here, similar calculation as in Fig. 17 and Fig. 18 examples can be performed for the case of three coils, and it is confirmed that if the three coils are arranged in the radial direction so that the current flow directions therein align
25 alternatively in positive and negative, the sum of absolute values of the coil magnetomotive force is minimized.

Because of size limitation of such as a cryostat and a low temperature vessel, necessary number of coils can not sometimes be disposed in the radial direction, in such instance, it is sufficient if a
5 coil is disposed along the inner wall of the low temperature vessel. The present invention discloses such generalized coil arrangement methods, and the specific examples thereof will be explained as embodiments hereinbelow.

10

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of an open type MRI device using a super conducting magnet according to the present invention;

15

Fig. 2 is a cross sectional view of a super conducting magnet representing an embodiment according to the present invention;

20

Fig. 3 is a cross sectional view of a super conducting magnet representing another embodiment according to the present invention;

Fig. 4 is a cross sectional view of a super conducting magnet representing still another embodiment according to the present invention;

Fig. 5 is a cross sectional view of a super
25 conducting magnet representing a further embodiment according to the present invention;

Fig. 6 is a cross sectional view of a super

conducting magnet representing a still further embodiment according to the present invention;

Fig. 7 is a cross sectional view of a super conducting magnet representing a still further
5 embodiment according to the present invention;

Fig. 8 is a cross sectional view of a super conducting magnet representing a still further embodiment according to the present invention;

Fig. 9 is a cross sectional view of a super
10 conducting magnet representing a still further embodiment according to the present invention;

Fig. 10 is a cross sectional view of a super conducting magnet representing a still further embodiment according to the present invention;

Fig. 11 is a cross sectional view of a super
15 conducting magnet representing a still further embodiment according to the present invention;

Fig. 12 is a cross sectional view of a super
conducting magnet representing a still further
20 embodiment according to the present invention;

Fig. 13 is a view for explaining an annular ring current;

Fig. 14 is a diagram showing a sensitivity curve of secondary degree irregular magnetic field intensity
25 produced by the annular ring current as shown in Fig. 13;

Fig. 15 is a view for explaining two annular ring

currents;

Fig. 16 is a diagram showing sensitivity curves of second degree irregular magnetic field intensity produced by the two annular ring currents as shown in
5 Fig. 15;

Fig. 17 is a diagram showing a numerical calculation example of a coil arrangement according to the present invention and contours of the magnetic field uniformity produced thereby;

10 Fig. 18 is a diagram showing a numerical calculation example of a coil arrangement according to the present invention and contours of the magnetic field uniformity produced thereby;

Fig. 19 is a diagram showing sensitivity curves
15 of irregular magnetic field intensities from second degree to 6th degree produced by the annular ring current as shown in Fig. 13;

Fig. 20 is three dimensional plots showing a space distribution of 6th degree irregular magnetic
20 field component;

Fig. 21 shows an optimum designed coil arrangement through computer programs so that the sum of absolute values of magnetomotive force is minimized according to the principle of the present invention;

25 Fig. 22 shows second degree irregular magnetic field components produced by the respective coils as shown in Fig. 21; and

Fig. 23 shows 4th degree irregular magnetic field components produced by the respective coils as shown in Fig. 21.

5 BEST MODES FOR CARRYING OUT THE PRESENT INVENTION

 Hereinbelow, embodiments of the present invention will be explained specifically with reference to Fig. 1 through Fig. 12.

 Fig. 1 is a perspective view of an open type
10 super conducting MRI device using a super conducting magnet representing an embodiment according to the present invention. Fig. 2 is a cross sectional view on z-x plane of the super conducting magnet 1 among many constituting elements of the open type MRI device
15 in Fig. 1.

 The MRI device as shown in Fig. 1 produces a uniform magnetic field in z axis direction in an open region 2 by upper and lower super conduction magnet assemblies 6 and 7, and permits MRI image taking at
20 the center portion of the open region 2. A patient 4 is carried by a bed and movable table 3 so that an image taking portion of the patient 4 positions at the center portion of the open region 2. The upper and lower super conducting magnetic assemblies 6 and 7 are
25 magnetically coupled by column shaped external ferromagnetic bodies 10 and are further designed so as to suppress leakage magnetic field. With thus

structured MRI, claustrophobia to which the patient 4 tends to be subjected during image taking is extremely reduced and the patient 4 can even be given an open space feeling, thereby, a psychological pressure of the patient 4 with respect to the image taking is greatly reduced. Further, an access of a medical doctor or an inspection engineer 5 to the patient 4 during the image taking can be facilitated significantly. In particular, an access of the medical doctor or the inspection engineer 5 to an object portion of the patient 4 during the image taking is permitted, therefore, an Interventional Radiology (IVR) is enabled which broadens possibility of medical treatment.

Further, as an advantage of the MRI device having the structure as shown in Fig. 1, since the direction of static magnetic field is orthogonal with respect to the longitudinal direction of a human body, a solenoid coil can be used for a probe for receiving NMR signals. The sensitivity of such solenoid type probe is theoretically 1.4 times higher than that of a saddle shaped or bird cage shaped probe used for the horizontal magnetic field type MRI device.

Accordingly, when assuming that the center magnetic field intensity is equal each other, the vertical magnetic field type MRI having the structure as shown in Fig. 1 can take a further accurate

tomographic images with a further higher speed in comparison with the conventional horizontal magnetic field type MRI device.

As has been mentioned above, the MRI device structured according to the concept as shown in Fig. 1 has a variety of advantages, however, a key for achieving a highly open space feeling from structural point of view is how to reduce the diameter of the upper and lower magnetic assemblies 6 and 7. The present invention exactly relates to the key and provides a magnet assembly structure of which outer diameter is small and of which production cost is inexpensive, and moreover which generates a desired uniform magnetic field.

Now, the structure of the magnet assemblies 6 and 7 will be explained with reference to Fig. 2. The upper and lower magnet assemblies 6 and 7 are surrounded at the outer circumferences thereof by respective ferromagnetic bodies so as to suppress leakage magnetic field. More specifically, disk shaped external ferromagnetic bodies 8 and 8' and cylindrical external ferromagnetic bodies 9 and 9' surround around upper and lower vacuum vessels 11 and 11', and the upper and lower ferromagnetic bodies 8, 8' and 9, 9' are magnetically coupled by the column shaped external ferromagnetic bodies 10. As the external ferromagnetic bodies used in the present

embodiment, any material will do, if such shows ferromagnetic property so that a variety of material can be used, however, in view of magnetic properties, cost and mechanical strength iron is generally preferable. Further, when a weight lightening of the ferromagnetic bodies is required, a material having a high permeability can be used. Through the surrounding of the circumferences with the external ferromagnetic bodies magnetic passages are formed for magnetic fluxes possibly leaking outside from the device to thereby suppress the leakage magnetic field from expanding far.

Main super conducting coils 13, 13', 14, 14', 15, 15' and 16, 16' are disposed substantially symmetric in upper and lower positions while sandwiching a uniform magnetic field region at the center of the magnet and substantially concentrically with respect to z axis, and produces a uniform magnetic field in vertical direction, namely in z axis direction. The upper and lower super conducting coils are disposed inside respective cooling containers 12 and 12', and the upper and lower cooling containers 12 and 12' are accommodated in respective vacuum vessels 11 and 11'. Further, for the sake of simplicity although the illustration in Fig. 2 is omitted, there is a structure for supporting the super conducting coils and further there is provided a heat shielding member

between the vacuum vessels and the cooling containers for preventing penetration of radiation heat. Liquid helium is stored inside the cooling vessels and cools the super conducting coils to a super low temperature of 4.2°K.

The upper and lower vacuum vessels are held by coupling tubes 17 disposed therebetween while keeping a predetermined distance. These coupling tubes 17 work to support mechanically the upper and lower vacuum vessels 11 and 11', however, can include a function of thermally connecting the upper and lower cooling containers. If such function is added, it becomes unnecessary to provide each one cryostat for upper and lower cooling containers, thereby, the system can be operated with a single cryostat. Further, the number of the coupling tubes 17 and the column shaped ferromagnetic bodies 10 needs not to be limited to two as illustrated, but can be increased three, four and more. Further, in order to obtain a further open space feeling a single support column forming an overhang structure can be used.

In the present embodiment, the respective four main super conducting coils 13, 13', 14, 14', 15, 15' and 16, 16' inside the respective upper and lower magnet assemblies are arranged so as to align their polarities alternatively in positive and negative. More precisely, when assuming a certain straight line

18 passing through the center of the magnet assemblies on any plane containing z axis representing the center axis of the magnet (herein, for the sake of explanation simplicity z-x plane is assumed) and when
5 the geometric center of the cross sections of the respective super conducting coils in the first quadrant on the z-x plane are projected on the straight line 18, the polarities of current flow of the projections on the straight line 18 corresponding
10 to the respective coils align alternatively in positive and negative. In other words, in the coil 16 a current is flown to the direction causing the main magnetic field and of which direction is assumed as the positive direction, a current in the negative
15 direction is flown in the coils 13 and 15, and a current in positive direction is flown in the coil 14.

Further, as seen from the drawing, the magnitude of absolute values of magnetomotive force of the respective coils 16, 15, 14 and 13 is larger in this
20 appearing order and it is understood that when the respective coils in the first quadrant on the z-x plane are projected on the straight line 18, the absolute values of magnetomotive force of the respective coils align in their order of magnitude.
25 Further, the absolute value of magnetomotive force of the coil 16 having the maximum average radius is the largest. These magnetomotive force setting method is

also one of the conditions which minimizes the sum of absolute values of magnetomotive force of the entire coils.

The positions and magnetomotive forces of the
5 respective coils are designed based on calculations so
as to form a uniform magnetic field distribution.
Although arrangement of coils which produces a uniform
magnetic field is infinite, however, the above
arrangement method as has been explained in the
10 Summary of the Invention gives the minimum sum of
absolute values of magnetomotive force, thereby, the
magnet can be produced with minimum cost. Further,
since the sum of absolute values of magnetomotive
force is small, the cross sectional areas of the
15 respective coils are reduced, thereby, the diameters
of the magnet assemblies can also be reduced. Still
further, the present embodiment is designed to render
the irregular magnetic field components from second
degree to 8th degree zero, and for this purpose four
20 coils are disposed in respective magnet assemblies.
As a result, a uniform magnetic field of 45cm dsv
(diameter of spherical volume) with ± 4 ppm variation
is obtained at the center of the magnet which
sufficiently fulfills the specification for a whole-
25 body MRI.

Hereinbelow, other embodiments according to the
present invention will be explained with reference to

the drawings.

Fig. 3 is a cross sectional view of a super conducting magnet for an open type MRI representing another embodiment according to the present invention.

5 The constitutional structure of the present embodiment is substantially the same as the super conducting magnet as shown in Figs. 1 and 2 except for a provision of super conducting shielding coils 29 and 29' for reducing the weight of the external

10 ferromagnetic bodies suppressing leakage magnetic field. According to general naming of leakage magnetic field shielding methods, the method of Fig. 2 embodiment is called as a passive shielding method and the method of Fig. 3 embodiment is called as a hybrid

15 shielding method. When the geometric centers of the cross sections of main super conducting coils 25, 25', 26, 26', 27, 27' and 28, 28' except for the super conducting shielding coils 29 and 29' in Fig. 3 on the z-x plane in the first quadrant are projected on a

20 straight line 30 (an imaginary line), the coils are arranged in such a manner that the current flow direction of the corresponding coils to the projections aligns alternatively in positive and negative on the straight line 30.

25 Fig. 4 is a cross sectional view of a super conducting magnet for an open type MRI device representing still another embodiment according to the

present invention. The present embodiment shows an active shielding type super conducting magnet. The present embodiment suppresses leakage magnetic field only by the shielding coils and eliminates ferromagnetic shielding bodies such as iron, therefore, the weight thereof is minimized. When the geometric centers of the cross sections of main super conducting coils 34, 34', 35, 35', 36, 36' and 37, 37' except for the super conducting shielding coils 39 and 39' in Fig. 4 on the z-x plane in the first quadrant are projected on a straight line 40, the coils are arranged in such a manner that the current flow direction of the corresponding coils to the projections aligns alternatively in positive and negative on the straight line 40.

In the above embodiment, the magnet assemblies are constituted basically to produce a uniform magnetic field by air-core coils and to suppress leakage magnetic field by the external ferromagnetic bodies or the shielding coils. Hereinbelow, embodiments according to the present invention which positively makes use of ferromagnetic bodies functioning as magnetic poles for producing the uniform magnetic field are disclosed. Figs. 5 through 12 are cross sectional views of super conducting magnets for an open type MRI representing further embodiments according to the present invention.

The magnet as shown in Fig. 5 is designed in such a manner that magnetic pole shaped ferromagnetic bodies 44 and 44' disposed inside disk shaped external ferromagnetic bodies 41 and 41' function to enhance the center magnetic field intensity and to reduce the share to be borne by the super conducting coils for the center magnetic field intensity as well as to reduce the sum of absolute values of magnetomotive force of the super conducting coils. Since the uniformity of magnetic field is primarily achieved by the arrangement of the super conducting coils and the division manner of their magnetomotive forces, the present arrangement is based on the principle of the present invention. Namely, where the geometric centers of the cross sections of main super conducting coils 48, 48', 49, 49', 50, 50' and 51, 51' in Fig. 5 on the z-x plane in the first quadrant are projected on a straight line 52, the coils are arranged in such a manner that the current flow direction of the corresponding coils to the projections aligns alternatively in positive and negative on the straight line 52.

In the magnet as shown in Fig. 6, the magnetic poles are further enlarged in comparison with the magnet as shown in Fig. 5 and the burden with regard to magnetomotive forces of super conducting coils is further reduced. The present embodiment is

constituted to optimize the shape of the magnetic poles and to produce a certain level of uniform magnetic field only with the magnetic poles. Accordingly, a small number of super conducting coils will do and in the present embodiment each two super conducting coils in respective upper and lower magnet assemblies can produce sufficient uniform magnetic field. As has been explained in the Summary of the Invention, the current flow direction of the two super conducting coils 60, 60' and 61, 61' are opposite each other, thereby, the second degree irregular magnetic field components are eliminated with the small magnet assemblies. Namely, a current is flown in the outside super conducting coils in the direction producing the main magnetic field. On the other hand, a current in the opposite direction is flown in the inside super conducting coils.

In the magnet as shown in Fig. 7, a rough uniform magnetic field is produced by the magnetic poles having an optimized configuration and three super conducting coils are disposed in the respective magnet assemblies so as to further enhance the uniformity of the magnetic field. The main super conducting coils 70, 70', 71, 71' and 72, 72' are arranged so as to produce a uniform magnetic field with a limited radius and with a minimum magnetomotive force in such a manner that the current flow direction of the

corresponding coils to the projections aligns alternatively in positive and negative on the straight line 73 as shown in Fig. 7 according to the principle of the present invention.

5 A magnet as shown in Fig. 8 is substantially the same as the magnet as shown in Fig. 7 except for the provision of super conducting shielding coils 84 and 84' for reducing the weight of the external ferromagnetic bodies for suppressing leakage magnetic
10 field. In the present embodiment, the main super conducting coils 81, 81', 82, 82' and 83, 83' except for the shielding coils 84 and 84' are arranged so as to produce a uniform magnetic field with a limited radius and with a minimum magnetomotive force in such
15 a manner that the current flow direction of the corresponding coils to the projections aligns alternatively in positive and negative on the straight line 85 as shown in Fig. 8 according to the principle of the present invention.

20 Figs. 9 and 10 are other embodiments of super conducting magnets for an open type MRI which produce a uniform magnetic field through combinations of magnetic poles and super conducting coils. The both magnets are principally constituted based on the
25 following concept that the magnetic poles functions to strengthen the center magnetic field intensity so as to save magnetomotive forces of the coils and the

uniformity of the magnetic field is achieved by the arrangement of the coils. Although the configuration of magnetic pole shaped ferromagnetic bodies 89, 89' and, 101, 101' is optimized, since the bodies are
5 located away from the center portion of the magnet serving as the image taking region, it is impossible to produce the uniform magnetic field only with modification of the magnetic pole configuration. Therefore, in Figs. 9 and 10 embodiments, with four
10 and three super conducting coils for each assembly a uniform magnetic field is produced. Further, in Fig. 10 embodiment, the outer circumferential portions of vacuum vessels 102 and low temperature containers 103 are expanded so as to receive the end portion coils
15 107 having a larger magnetomotive forces. Further, with such configuration, the magnetic pole shaped ferromagnetic bodies 101 and 101' can be located near to the image taking region, thereby the share borne by the magnetic poles for strengthening the center
20 magnetic field intensity can be increased, thus the magnetomotive force to be borne by the super conducting coils is saved. The main super conducting coils in both embodiments are arranged so as to produce a uniform magnetic field with a limited radius
25 and with a minimum magnetomotive force in such a manner that the current flow direction of the corresponding coils to the projections aligns

alternatively in positive and negative on the straight line 97 or x axis 108 as shown in Fig. 9 or 10 according to the principle of the present invention.

Figs. 11 and 12 show further embodiments in which
5 ferromagnetic body elements are disposed inside the low temperature containers primarily for reducing the magnetomotive forces to be induced by the coils. With regard to leakage magnetic field suppressing method, Fig. 11 embodiment uses a passive shielding method and
10 Fig. 12 embodiment uses an active shielding method. Inner ferromagnetic bodies 119, 119', 120, 120' and 131, 131', 132, 132' are formed in an annular ring shape and are disposed respectively between super conducting coils. When disposing these ferromagnetic
15 body elements in such position, the magnetomotive forces to be induced by the coils can be effectively reduced. Likely, in the present embodiments, the super conducting coils constituting the main coils are arranged so as to produce a uniform magnetic field
20 with a limited radius and with a minimum magnetomotive force in such a manner that the current flow direction of the corresponding coils to the projections aligns alternatively in positive and negative on the straight line 122 or 133 as shown in Fig. 11 or 12 according to
25 the principle of the present invention.

Hitherto, the present invention has been explained with reference to the concrete embodiments.

In the above embodiments, all of the coils were super conducting coils, however, the coils according to the present invention are not limited to the super conducting coils. For example, coils using copper
5 wires can be used, further, any materials which carry current can be acceptable. For the present invention a variety of embodiments can be conceived a part of which has been explained above, therefore, the present invention should never be limited to the specific
10 embodiments disclosed.

As has been explained hitherto, according to the present invention, a super conducting magnet, device for an open type MRI which is provided with a broad opening and is obtainable a broad uniform magnetic
15 field production region with a high magnetic field intensity and with less leakage magnetic field and being stable in time, is further improved which provides a further higher open space feeling and permits a desirable access to a patient representing
20 an inspection object through reducing the diameter of the magnet which also permits manufacturing cost reduction.

Further, according to the present invention, an MRI device can be realized which provides a higher
25 open feeling and permits a desirable access to an inspection object.

[illegible][illegible]

CLAIMS:

1. A magnet device in which two sets of static magnetic field generation sources, each being constituted by current carrying means disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with at least four current carrying means, characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line.

2. A magnet device in which two sets of static magnetic field generation sources, each being constituted by current carrying means and shielding current carrying means for suppressing leakage magnetic field to an external region disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite

region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with at least four current carrying means and at least one shielding current carrying means, characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line.

3. A magnet device in which two sets of static magnetic field generation sources, each being constituted by current carrying means disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with a ferromagnetic body functioning as a magnetic pole and at least two current carrying means, characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis

orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line.

4. A magnet device in which two sets of static magnetic field generation sources, each being constituted by current carrying means and shielding current carrying means for suppressing leakage magnetic field to an external region disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with a ferromagnetic body functioning as a magnetic pole, at least two current carrying means and at least one shielding current carrying means, characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner

that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line.

5 5. A magnet device in which two sets of static magnetic field generation sources, each being constituted by current carrying means disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with three current carrying means, characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line.

6. A magnet device in which two sets of static magnetic field generation sources, each being constituted by current carrying means and shielding current carrying means for suppressing leakage

magnetic field to an external region disposed substantially concentrically with respect to a first direction in order to generate a uniform magnetic field directing in the first direction in a finite region, are disposed facing each other while placing the uniform magnetic field region therebetween and each of the static magnetic field generation sources is provided with three current carrying means and at least one shielding current carrying means, characterized in that when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line.

7. A magnet device according to one of claims 1-4, characterized in that when the geometric centers of the cross sections of the current carrying means are projected on the first straight line on the first plane, the absolute values of magnetomotive force of the current carrying means in the respective static magnetic field generation sources at the corresponding projections align on the first straight line in either descending order or ascending order.

8. A magnet device according to claim 5-6, characterized in that when the geometric centers of the cross sections of the current carrying means are projected on the second axis on the first plane, the absolute values of magnetomotive force of the current carrying means in the respective static magnetic field generation sources at the corresponding projections align on the second axis in either descending order or ascending order.

9. A magnet device according to one of claims 1-8, characterized in that in each of the static magnetic field generation sources, the absolute values of magnetomotive force of the current carrying means having the largest average radius among the current carrying means is larger than the absolute values of the magnetomotive force of other currently carrying means.

10. A magnet device according to one of claims 1-9, characterized in that each of the static magnetic field generation sources includes at least one ferromagnetic body which helps formation of the magnetic field.

11. A magnet device according to claim 10, characterized in that the ferromagnetic body functions as a magnetic pole.

12. A magnet device according to one of claims 1-11, characterized in that the magnetic device further comprises an external ferromagnetic body which covers the outside of the two sets of static magnetic field generation sources and forms a magnetic passage to suppress leakage magnetic field.

13. A magnet device according to claim 12, characterized in that the external ferromagnetic body includes a disk shaped ferromagnetic body and a column shaped ferromagnetic body.

14. A magnet device according to one of claims 1-13, characterized in that the current carrying means is constituted by a material having a super conducting property, and the two sets of static magnetic field generation sources includes a cooling means which cools the current carrying means to a temperature at which the current carrying means shows the super conducting property and maintains the same at the temperature.

15. An MRI device which uses the magnet device according to one of claims 1-14.

16. An MRI device including the magnet device according to one of claims 1-14, which applies the magnetic field in such a manner that the main magnetic flux direction is perpendicular with respect to the face of a stand on which a measurement object is laid.

17. A super conducting magnetic device for an open and vertical magnetic field type MRI device including a first and a second static magnetic field generation source which are disposed in vertical direction opposing each other while sandwiching a space for receiving a person to be inspected, each of the first and second static magnetic field generation sources includes static magnetic field generation use coil units of equal to or more than three which are arranged concentrically around the center axis in vertical direction thereof, characterized in that, the directions of DC current flow in the static magnetic field generation use coil units of equal to or

more than three in each of the static magnetic field generation sources are determined alternative in positive and negative direction with reference to projection positions of geometric centers of cross sections of the respective coil units of equal to or more than three on a straight line passing through a crossing point, on a plane which is perpendicular to the central axis in vertical direction and contains a horizontal axis having an equal distance both from the first and second static magnetic field generation sources, of the center axis and the horizontal axis and at the side of the straight line away from the horizontal axis when viewed from the respective coil units of equal to or more than three.

18. A super conducting magnet device for an open and vertical magnetic field type MRI device including a pair of static magnetic field generation sources which are disposed in vertical direction opposing each other while sandwiching a space having a broad opening for receiving a person to be inspected, and each of the pair of static magnetic field generation sources includes a main coil unit for the static magnetic field generation having first diameter and being disposed concentrically with the center axis in vertical direction thereof, a plurality of coil units for irregular magnetic field correction each having a diameter smaller than the first diameter and being likely disposed concentrically with the center axis in vertical direction thereof and shielding coil unit for suppressing magnetic field leakage having substantially the same diameter as the first diameter and being disposed concentrically with the center axis in vertical direction thereof but being located distant position than the main coil unit for static magnetic field generation with respect to the space, characterized in that, the directions of DC current flow in the main coil unit for static magnetic field generation and the plurality of coil units for irregular magnetic filed

correction in each of the static magnetic field generation sources are determined alternative in positive and negative direction with reference to projection positions of geometric centers of cross sections of the main coil unit for static magnetic field generation and the plurality of the coil units for irregular magnetic field correction on a straight line passing through a crossing point, on a plane which is perpendicular to the center axis in vertical direction and contains a horizontal axis having an equal distance both from the first and second static magnetic field generation sources, of the center axis and the horizontal axis and at the side of the straight line away from the horizontal axis when viewed from the main coil unit for static magnetic field generation and the plurality of coil units for irregular magnetic field correction, as well as the direction of DC current flow in the shielding coil unit is determined to be opposite to the direction of the DC current flow in the main coil unit for static magnetic field generation.

19. A magnetic device including a pair of static magnetic field generation sources for generating a uniform magnetic field directing in a first direction in a finite region each of the static magnetic field generation sources being provided with at least two current carrying means disposed concentrically, characterized in that, the at least two current carrying means are disposed concentrically while being spaced each other and further when assuming a crossing point of a first axis which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the respective static magnetic field generation sources as a first point, the current carrying means are disposed in such a manner that when geometrical centers of cross sections of the current carrying means are projected on a first straight line on a

first plane containing the first axis, the second axis and the first point and passing through the first point, the current carrying means at the respective corresponding projections aligns alternatively in positive and negative direction on the first straight line.

20. A super conducting magnetic device for an open and vertical magnetic field type MRI
5 device including a first and a second static magnetic field generation source which are disposed
opposing each other while sandwiching a space for receiving a person to be examined, each of
the first and second static magnetic field generation sources includes static magnetic field
generation use coil units of equal to or more than three which are arranged concentrically with
the central axis passing through the center thereof, characterized in that, the static magnetic field
10 generation use coil units of equal to or more than three in each of the static magnetic field
generation sources are arranged in such a manner that within an angle range defined by a first
line segment on a plane containing the center axis and extending in a direction perpendicular to
the center axis from a center point on the center axis having substantially the same distance from
both first and second static magnetic field generation sources and a second line segment extending
15 from the center point toward the static magnetic field generation use coil unit located most inside
and most close with respect to the space within the plane, when the geometric centers of the cross
sections of the respective static magnetic field generation use coil units are projected on any
straight line while locating the first line segment therebetween, the current flow directions of the
static magnetic field generation use coil units at the respective corresponding projection points
20 align alternatively in positive and negative direction on the straight line.

21. A super conducting magnet device for an open and vertical magnetic field type MRI device including a pair of static magnetic field generation sources which are disposed opposing each other while sandwiching a space having a broad opening for receiving a person to be examined, and each of the pair of static magnetic field generation sources includes a main coil unit for the static magnetic field generation having a first diameter and being disposed concentrically with the center axis passing the center of the static magnetic field generation sources, a plurality of coil units for irregular magnetic field correction each having diameter smaller than the first diameter and being disposed concentrically with the center axis thereof and a shielding coil unit for suppressing magnetic field leakage having substantially the same diameter as the first diameter and being disposed concentrically with the center axis thereof but being located distant position than the main coil unit for static magnetic field generation with respect to the space, characterized in that, the main coil unit for static magnetic field generation and the plurality of coil units for irregular magnetic field correction in each of the static magnetic field generation sources are arranged in such a manner that within an angle range defined by a first line segment on a plane containing the center axis and extending in a direction perpendicular to the center axis from a center point on the center axis having substantially the same distance from both first and second static magnetic field generation sources and a second line segment extending from the center point toward the coil unit for irregular magnetic field correction located most inside and most close with respect to the space within the plane, when the geometric centers of the cross sections of the main coil unit for static magnetic field generation and the plurality of unit coils for irregular magnetic field correction are projected on any straight line while locating the first line segment therebetween, the current flow directions of the main coil unit for static magnetic field



5

ABSTRACT OF THE DISCLOSURE



A magnet device which includes two sets of static magnetic field generation sources, each being
5 constituted by current carrying means disposed concentrically in order to generate a uniform magnetic field directing in a first direction being provided with at least four current carrying means, and in which when assuming a crossing point of a first axis
10 which is in parallel with the first direction and passes substantially the center of the current carrying means and a second axis which crosses the first axis orthogonally and locates at substantially the equal distance from the two sets of the static
15 magnetic field generation sources as a first point and further assuming a first straight line contained on a first plane defined by the first axis, the second axis and the first point and passing through the first point, the current carrying means are disposed in such
20 a manner that, when geometrical centers of cross sections of the current carrying means on the first plane are projected on the first straight line, the current carrying direction of the current carrying means at the respective corresponding projections of
25 each of the static magnetic field generation sources aligns alternatively in positive and negative direction on the first straight line, thereby, an open

[illegible]



1/12

Fig. 1**Fig. 2**

2/12



Fig. 3**Fig. 4**

3/12



Fig. 5**Fig. 6**

4/12



4/12

Fig. 7**Fig. 8**



5/12

Fig. 9**Fig. 10**



6/12

Fig. 11**Fig. 12**



7/12

Fig. 13**Fig. 14**



8/12

Fig. 15**Fig. 16**



9/12

Fig. 17**Fig. 18**


10/12

Fig. 19**IRREGULAR MAGNETIC
FIELD INTENSITY****Fig. 20**

11/12

Fig. 21**Fig. 22**

12/12

Fig. 23

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

Japanese Language Declaration

(日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に枠内をマークすることで、示しています

Prior Foreign Application(s)

外国での先行出願

PCT/JP98/05406

JAPAN

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

(Number)

(番号)

(Country)

(国名)

01.12.98

(Day/Month/Year Filed)

(出願年月日)

☐

(Number)

(番号)

(Country)

(国名)

(Day/Month/Year Filed)

(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日より本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status Patented, Pending, Abandoned)

(現況：特許許可済、係属中、放棄済)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status Patented, Pending, Abandoned)

(現況：特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じているところに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は共に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995 no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

MAGNET APPARATUS AND MRI APPARATUS

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約
国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1章56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

委任状：私は下記の発明者として、本出願に関する一切の手続きを米特許審判局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Ivan S. Kavrukov (Reg. No. 25161), Thomas F. Moran (Reg. No. 16579); Christopher C. Dunham (Reg. No. 22031); Norman H. Zivin (Reg. No. 25385), John P. White (Reg. No. 28678); Robert D. Katz (Reg. No. 30141); Peter J. Phillips (Reg. No. 29691); Richard S. Milner (Reg. No. 33970); Richard F. Jaworski (Reg. No. 33515); and Paul Teng (Reg. No. 40837)

書類送付先

Send Correspondence to:

Ivan S. Kavrukov, Esq.
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Ivan S. Kavrukov, Esq.
Tel. (212) 278-0400

唯一または第一発明者名 KAKUGAWA Shigeru		Full name of sole or first inventor	
発明者の署名 Shigeru Kakugawa	日付 4/5/2000	Inventor's signature	Date
住所 17-2-206, Moriyama-cho 3-chome,		Residence Hitachi-shi, Ibaraki JAPAN	
国籍 Japanese		Citizenship JPX	
私書箱		Post Office Address	
第二共同発明者 KITAMURA Shouji		Full name of second joint inventor if any	
第二共同発明者の署名 Masashi Kitamura	日付 3/31/2000	Second inventor's signature	Date
住所 72-9, Keyakidai 1-chome, Mito-shi,		Residence JPX Ibaraki JAPAN	
国籍 Japanese		Citizenship	
私書箱		Post Office Address	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration (日本語宣言書)

委任状：私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Ivan S. Kavrukov (Reg. No. 25161), Thomas F. Moran (Reg. No. 16579); Christopher C. Dunham (Reg. No. 22031); Norman H. Zivin (Reg. No. 25385), John P. White (Reg. No. 28678); Robert D. Katz (Reg. No. 30141); Peter J. Phillips (Reg. No. 29691); Richard S. Milner (Reg. No. 33970); Richard F. Jaworski (Reg. No. 33515); and Paul Teng (Reg. No. 40837)

書類送付先

Send Correspondence to:

Ivan S. Kavrukov, Esq.
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Ivan S. Kavrukov, Esq.
Tel. (212) 278-0400

Third

唯一または第一発明者名 <u>HARA Nobuhiro</u>	Full name of sole or first inventor		
発明者の署名 <u>Nobuhiro Hara</u>	日付 <u>4/5/2000</u>	発明者の署名	Date
住所 <u>9-8, Mizuki-cho 1-chome, Hitachi-shi, Ibaraki JAPAN</u>	Residence		
国籍 <u>Japanese</u>	Citizenship <u>JPK</u>		
私書箱	Post Office Address		
第二共同発明者 <u>KOMURA Akiyoshi</u>	Full name of second joint inventor if any		
第二共同発明者 <u>Akiyoshi Komura</u>	日付 <u>4/10/2000</u>	Second inventor's signature	Date
住所 <u>20-1, Mizuki-cho 2-chome, Hitachi-shi, Ibaraki JAPAN</u>	Residence <u>JPK</u>		
国籍 <u>Japanese</u>	Citizenship		
私書箱	Post Office Address		

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

(日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁護士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Ivan S. Kavrukov (Reg. No. 25161), Thomas F. Moran (Reg. No. 16579); Christopher C. Dunham (Reg. No. 22031); Norman H. Zivin (Reg. No. 25385), John P. White (Reg. No. 28678); Robert D. Katz (Reg. No. 30141); Peter J. Phillips (Reg. No. 29691); Richard S. Milner (Reg. No. 33970); Richard F. Jaworski (Reg. No. 33515); and Paul Teng (Reg. No. 40837)

書類送付先

Send Correspondence to:

Ivan S. Kavrukov, Esq.
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Ivan S. Kavrukov, Esq.
Tel. (212) 278-0400

第五 唯一または第一発明者名 HINO Noriaki		Full name of sole or first inventor	
発明者の署名 Noriaki Hino	日付 3/31/2000	Inventor's signature	Date
住所 1433-11, Miwa 3-chome, Mito-shi, Ibaraki JAPAN		Residence	
国籍 Japanese		Citizenship	JPX
私書箱		Post Office Address	
第六 第二共同発明者 KAWANO Hajime		Full name of second joint inventor if any	
第二共同発明者 Hajime Kawano	日付 2/23/2000	Second inventor's signature	Date
住所 #6-108, 663, Ichige, Hitachinaka-shi, Ibaraki JAPAN		Residence	
国籍 Japanese		Citizenship	JPX
私書箱		Post Office Address	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Ivan S. Kavrukov (Reg. No. 25161), Thomas F. Moran (Reg. No. 16579); Christopher C. Dunham (Reg. No. 22031); Norman H. Zivin (Reg. No. 25385), John P. White (Reg. No. 28678); Robert D. Katz (Reg. No. 30141); Peter J. Phillips (Reg. No. 29691); Richard S. Milner (Reg. No. 33970); Richard F. Jaworski (Reg. No. 33515); and Paul Teng (Reg. No. 40837)

書類送付先

Send Correspondence to:

Ivan S. Kavrukov, Esq.
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Ivan S. Kavrukov, Esq.
Tel. (212) 278-0400

第七	
唯一または第一発明者名 HONMEI Takao	Full name of sole or first inventor
発明者の署名 Honmei Takao	Inventor's signature
日付 2000/2/16	Date
住所 885-16, Ichige, Hitachinaka-shi, Ibaraki JAPAN	Residence
国籍 Japanese	Citizenship JPY
私書箱	Post Office Address
第八	
第二共同発明者 TAKESHIMA Hirotaka	Full name of second joint inventor, if any
第二共同発明者 Hirotaka Takeshima	Second inventor's signature
日付 2000/3/16	Date
住所 3-1, Koshiba 4-chome, Ryugasaki-shi, Ibaraki JAPAN	Residence
国籍 Japanese	Citizenship JPY
私書箱	Post Office Address

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

Japanese Language Declaration

(日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許審判局に対して遂行する弁護士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Ivan S. Kavrukov (Reg. No. 25161), Thomas F. Moran (Reg. No. 16579); Christopher C. Dunham (Reg. No. 22031); Norman H. Zivin (Reg. No. 25385), John P. White (Reg. No. 28678); Robert D. Katz (Reg. No. 30141); Peter J. Phillips (Reg. No. 29691); Richard S. Milner (Reg. No. 33970); Richard F. Jaworski (Reg. No. 33515); and Paul Teng (Reg. No. 40837)

書類送付先

Send Correspondence to:

Ivan S. Kavrukov, Esq.
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036

直接電話連絡先 名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Ivan S. Kavrukov, Esq.
Tel. (212) 278-0400

唯一または第一発明者名		Full name of sole or first ^{ninth} inventor	
YATSUO Takeshi			
発明者の署名	日付	Inventor's signature	Date
<i>Takeshi Yatsu</i>	2000/3/16		
住所		Residence	
1-8, Chiyoda 3-chome, Kashiwa-shi, Chiba JAPAN			
国籍		Citizenship	
Japanese		JPX	
私書箱		Post Office Address	
第二共同発明者		Full name of second ^{tenth} joint inventor, if any	
TAZAKI Hiroshi			
第二共同発明者	日付	Second inventor's signature	Date
<i>Hiroshi Tazaki</i>	2000/3/16		
住所		Residence	
#405, 17-4, Kooda, Kashiwa-shi, Chiba JAPAN		JPX	
国籍		Citizenship	
Japanese			
私書箱		Post Office Address	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)